



SUPERMINI LONG

SUPERMINI LONG TRAILER

Features

- TARE WEIGHT OF ONLY 13,500#!
- UP TO 50,500#+ LEGAL PAYLOAD*
- HIGH UPTIME TRAILER
- CARRIES UP TO 30' LONG CONTAINERS
- FAST SINGLE REEVING & DUAL LIFT CYLINDERS W/60,000#
- ALL CYLINDER RODS CHROME PLATED
- 10" x 4" x 3/8" 50,000# MIN. YIELD UPPER FRAME
- 4" SIDE ROLLERS MOUNTED PIN THROUGH TUBE, WITH ROLL PINS
- REEVING SLIDE PLATE W/GREASABLE SIDE ROLLERS
- 80,000# MIN. YIELD FABRICATED WIDE FLANGE LOWER FRAME
- BRAND NAME SPRING SUSPENSION RATED @ 25,000# PER AXLE
- BRAND NAME AXLES RATED @ 25,000# EACH, SYNTHETIC GREASE
- 102" WIDE AXLES
- HOLLAND LANDING GEAR
- QUARTER REAR STEEL DIAMOND PLATE FENDERS
- GREASABLE GROOVED BRONZE BUSHED ROLLERS & SHEAVES
 LED LIGHTS
- HEAVY WALL 1" CHROMIUM TRIVALENT PLATED HYD. TUBING
- PARKER 1" TOUGH COVER HYDRAULIC HOSES RATED 3,000 PSI
- SECONDARY IN-LINE ABS FILTER
- 10 BOLT HUB PILOTED STEEL WHEELS
- 11R22.5 STEEL BELTED TIRES, 16 PLY RATED
- SANDBLAST, PRIME AND PAINT WITH INDUSTRIAL ENAMEL
- BRAKE CONTROL-SPRING LOADED
- MAIN CONTROL VALVE-DISTANCED FROM OPERATOR
- CABLE 7/8" SECURED WITH BECKET
- KING PIN WITH GREASE ZERKS
- PRESSURE GAUGE

Benefits

EXTREMELY LIGHT; MAXIMIZES LEGAL PAYLOAD PAYLOADS MUCH MORE THAN ROLL OFF TRUCK TRACTOR/TRAILER MEANS HIGH EQUIP. UTILIZATION CARRIES LARGE BOXES REDUCES MAINTENANCE BY 50%. LESS WEIGHT. LONGER LIFE AND EASE OF REBUILD EXCEEDS INDUSTRY STANDARD OF 8", ADDS STRENGTH ROBUST DESIGN, NO WELDED PLATE TO BREAK OFF LONG LIFE, REDUCES FRICTION, INCREASES CAPACITY DESIGNED FOR MAXIMUM CAPACITY, LONGER LIFE PARTS AVAILABLE NATIONWIDE 10% STRONGER THAN INDUSTRY STANDARD, LOW MAINT. MORE STABILITY LIGHTER TARE WEIGHT LIGHT WEIGHT YET VERY DURABLE SMOOTHER OPERATION; LONGER LIFE MOISTURE AND VIBRATION RESISTANT, LONGER LIFE CORROSION RESISTANT, ADDS LIFE, SPEED TO SYSTEM RESISTS ABRASION, ADDS LIFE, SPEED TO SYSTEM ADDS 100,000 MILES OR 1 YEAR TO ABS WARRANTY INDUSTRY STANDARD; AVAILABLE NATIONWIDE INDUSTRY STANDARD; AVAILABLE NATIONWIDE LONG LASTING, DURABLE FINISH ADDED SAFETY, REDUCES LOAD & UNLOAD TIME ADDED SAFETY, PROTECTION SAFETY AND REDUCED MAINTENANCE EASY MAINTENANCE, LONGER PLATE LIFE SIMPLE CHECK OF HYDRAULIC SYSTEM

*BASED ON STATES ALLOWING 80,000# GVW w/16,000# TRACTOR, FEDERAL BRIDGE LAW MAY APPLY; (including container)

